

PACKING INSTRUCTION Y344

STATE VARIATIONS: BEG-03, SAG-01, USG-04

OPERATOR VARIATIONS: AM-03, CX-02, DE-01, FX-17, GA-03, GF-04, IJ-12, KA-02, KE-07, KQ-08, LC-02, LD-02, LH-01, LX-02, LY-04, MH-14, MX-03, OM-04, OU-04, PX-10, QA-03, SW-02, TN-04, UX-02, XK-03

The instruction applies for Limited Quantities of flammable liquids with no subsidiary risk in Packing Group III.

The General Packing Requirements of Subsections 5.0.2 to 5.0.4 (with the exception of 5.0.2.3, 5.0.2.5, 5.0.2.11(f), 5.0.2.11(g) and 5.0.2.14.2) must be met except that the packagings do not have to meet the marking and testing requirements of 6.0.4 and Subsection 6.3. Packagings must meet the construction criteria specified in Subsections 6.1 and 6.2 and the test criteria specified in Subsection 6.6.

Compatibility Requirements

- substances must be compatible with their packagings as required by 5.0.2.6.

Closure Requirements

- closures must meet the requirements of 5.0.2.7.

Limited Quantity Requirements

The requirements of Subsection 2.7 must be met including:

- the capability of the package to pass a drop test of 1.2 m;
- a 24 hour stacking test;
- inner packagings for liquids must be capable of passing a pressure differential test (5.0.2.9)

the gross weight of the completed package must not exceed 30 kg (66 lb).

Single packagings are not permitted.

COMBINATION PACKAGINGS		
Inner Packaging (see 6.1)	Net quantity per inner packaging	Total net quantity per package
Glass	2.5 L	10.0L
Metal	5.0 L	
Plastic	5.0 L	

OUTER PACKAGINGS																
Type	Drums						Jerricans			Boxes						
Desc.	Steel	Aluminum	Ply-wood	Fibre	Plastic	Other Metal	Steel	Aluminum	Plastic	Steel	Aluminum	Wood	Ply-wood	Reconstituted wood	Fibre-board	Plastic

PACKING INSTRUCTION 355

STATE VARIATIONS: BEG-03, USG-04/13

OPERATOR VARIATIONS: 5X-02, AA-01, AM-03, AS-02, AY-04, BA-01, BW-01, CA-10, CO-03/06, CS-03/06, CX-02/03, EI-01, EY-03, FX-02/17, JL-09, KA-02/03, KC-06, KE-07, KZ-07, LC-02, LD-02/03, LY-04, MK-12, MX-03, NH-06, OK-04, QA-03, SK-04, TG-02, UA-01, UX-04

The instruction applies to flammable liquids with no subsidiary risk or a subsidiary risk of Division 6.1 in Packing Group III on passenger aircraft.

The General Packing Requirements of 5.0.2 must be met.

Compatibility Requirements

- substances must be compatible with their packagings as required by 5.0.2.6.

Closure Requirements

- closures must meet the requirements of 5.0.2.7.

Combination and single packagings are permitted.

COMBINATION PACKAGINGS		
Inner Packaging (see 6.1)	Net quantity per inner packaging	Total net quantity per package
Glass	2.5 L	60.0L
Metal	10.0 L	
Plastic	10.0 L	

OUTER PACKAGINGS

Type	Drums						Jerricans			Boxes						
Desc.	Steel	Aluminum	Plywood	Fibre	Plastic	Other Metal	Steel	Aluminum	Plastic	Steel	Aluminum	Wood	Plywood	Reconstituted wood	Fibre-board	Plastic
Spec.	1A2	1B2	1D	1G	1H2	1N2	3A2	3B2	3H2	4A	4B	4C1 4C2	4D	4F	4G	4H1 4H2

SINGLE PACKAGINGS

Type	Drums				Jerricans			Composites	Cylinders
Desc.	Steel	Aluminium	Plastic	Other metal	Steel	Aluminium	Plastic	Plastic	
Spec.	1A1 1A2	1B1 1B2	1H1 1H2	1N1 1N2	3A1 3A2	3B1 3B2	3H1 3H2	All	As permitted in 5.0.6.6